

**Blast Off**

**PRODUCT CODE:**

51055, 51030, 51015, 5105

**DESCRIPTION:**

High active foaming alkaline presoak. Contains additional solvents for difficult cleaning situations. Recommended for use in soft water.

**PRODUCT APPLICATION:**

Presoak, Tire Cleaner, Wheel Cleaner

**DILUTION RECOMMENDATIONS:**

Presoak  
Tire and Wheel Cleaner

**Standard**

60-120:1  
10-30:1

**STANDARD PRODUCT**

**Step 1:** Fill graduated cylinder to **5 ml.** mark with solution.

**Step 2:** Add **4** drops Indicator **P**. Solution will turn pink.

**Step 3:** Add Titrate **#1** dropwise. Invert tube to mix after each drop.

**Step 4:** Continue adding drops until solution turns colorless.

**Dilution Range:** 200:1 – 30:1  
**Indicator:** P  
**Titrate #:** 1

| <u># DROPS</u> | <u>OZ.PER GAL.</u> | <u>RATIO</u> |
|----------------|--------------------|--------------|
| 4              | 0.64               | 200:1        |
| 5              | 0.92               | 139:1        |
| 6              | 1.20               | 107:1        |
| 7              | 1.48               | 86:1         |
| 8              | 1.76               | 73:1         |
| 9              | 2.04               | 63:1         |
| 10             | 2.32               | 55:1         |
| 11             | 2.60               | 49:1         |
| 12             | 2.88               | 44:1         |
| 13             | 3.16               | 41:1         |
| 14             | 3.44               | 37:1         |
| 15             | 3.72               | 34:1         |
| 16             | 4.00               | 32:1         |
| 17             | 4.28               | 30:1         |