



HP300

PRODUCT CODE:

BE835

PRODUCT APPLICATION:

Presoak, Tire Cleaner, Wheel Cleaner

DESCRIPTION:

Hard water compatible alkaline system cleaner. Formulated with a combination of alkaline cleaners, water conditioning agents and premium surfactants to effectively remove tough road soils in hard water conditions. Hard water stable up to 300:1 at 10 grains hard.

DILUTION RECOMMENDATIONS:

Presoak
Tire and Wheel Cleaner

BULLSEYE

500-300:1
30-60:1

BULLSEYE

Step 1: Fill graduated cylinder to **10 ml.** mark with solution.

Step 2: Add **4** drops Indicator **P.** Solution will turn pink.

Step 3: Add Titrate **#1** dropwise. Invert tube to mix after each drop.

Step 4: Continue adding drops until solution turns colorless.

Dilution Range: 500:1 – 100:1

Indicator: P

Titrate #: 1



<u># DROPS</u>	<u>OZ.PER GAL.</u>	<u>RATIO</u>
5	0.26	500
6	0.34	378
7	0.42	307
8	0.50	258
9	0.57	223
10	0.65	196
11	0.73	175
12	0.81	158
13	0.89	144
14	0.97	132
15	1.05	122
16	1.12	114
17	1.20	106
18	1.28	100