



Power Wash™

PRODUCT CODE:

570240

DESCRIPTION:

Powdered foaming alkaline presoak. For use in high pressure and presoak applications as well as a single step tire and wheel cleaner.

PRODUCT APPLICATION:

High Pressure, Presoak, Tire Cleaner

DILUTION RECOMMENDATIONS:

High Pressure
Presoak
Tire Cleaner

Standard

300-400:1
60-120:1
6:1

STANDARD PRODUCT

Step 1: Fill graduated cylinder to **5 ml.** mark with solution.

Step 2: Add **4** drops Indicator **P.** Solution will turn pink.

Step 3: Add Titrate #**1** dropwise. Invert tube to mix after each drop.

Step 4: Continue adding drops until solution turns colorless.

Dilution Range: **1000:1 – 50:1**
Indicator: **P**
Titrate #: **1**

# DROPS	OZ.PER GAL.	RATIO
2	0.13	1000:1
3	0.20	635:1
4	0.27	469:1
5	0.34	372:1
6	0.42	308:1
7	0.49	263:1
8	0.56	229:1
9	0.63	203:1
10	0.70	182:1
11	0.77	166:1
12	0.85	152:1
13	0.92	140:1
14	0.99	130:1
15	1.06	121:1
16	1.13	113:1
17	1.20	106:1
18	1.27	100:1
20	1.42	90:1
23	1.63	80:1
26	1.85	70:1
30	2.13	60:1
36	2.56	50:1