



Presoak 100

PRODUCT CODE:

BE915

DESCRIPTION:

Presoak 100 high foaming low pH presoak and detergent effectively replaces traditional HF, ABF and other acid cleaners. In addition Presoak 100 breaks down key components in road film which traditional acids do not do.

PRODUCT APPLICATION:

Presoak

DILUTION RECOMMENDATIONS:

Presoak

BULLSEYE
180-360:1

BULLSEYE

Step 1: Fill graduated cylinder to **5 ml.** mark with solution.

Step 2: Add 4 drops Indicator P. No color change will occur.

Step 3: Add Titrate #3 dropwise. Invert tube to mix after each drop.

Step 4: Continue adding drops until solution turns pink.

Dilution Range: 300:1 - 80:1

Indicator: P

Titrate #: 3



<u># DROPS</u>	<u>OZ.PER GAL.</u>	<u>RATIO</u>
8	0.43	300
9	0.49	264
10	0.55	236
11	0.60	212
12	0.66	194
13	0.72	178
14	0.78	164
15	0.84	154
16	0.89	144
17	0.96	134
18	1.01	126
19	1.07	120
20	1.13	114
21	1.19	108
22	1.25	102
23	1.31	98
24	1.37	94
25	1.42	90
26	1.48	86
27	1.54	84
28	1.60	80