



Presoak 750

PRODUCT CODE:

BE855

DESCRIPTION:

Multipurpose foaming alkaline presoak. For use as a presoak in touchless & tunnel cleaning applications and as a single step tire and wheel cleaner.

PRODUCT APPLICATION:

Presoak, Tire Cleaner, Wheel Cleaner

DILUTION RECOMMENDATIONS:

Presoak
Tire and Wheel Cleaner

BULLSEYE

180-360:1
30-60:1

BULLSEYE

Step 1: Fill graduated cylinder to **5 ml.** mark with solution.

Step 2: Add **4** drops Indicator **P**. Solution will turn pink.

Step 3: Add Titrant **#2** dropwise. Invert tube to mix after each drop.

Step 4: Continue adding drops until solution turns colorless.

Dilution Range: 500:1 - 100:1

Indicator: P

Titrate #: 2



<u># DROPS</u>	<u>OZ.PER GAL.</u>	<u>RATIO</u>
10	0.26	500:1
11	0.29	449:1
12	0.31	407:1
13	0.34	372:1
14	0.37	343:1
15	0.40	318:1
16	0.43	297:1
17	0.46	278:1
18	0.49	261:1
19	0.52	246:1
20	0.55	233:1
21	0.58	222:1
22	0.61	211:1
23	0.64	201:1
24	0.67	192:1
25	0.69	184:1
26	0.72	180:1
27	0.75	170:1
29	0.81	160:1
31	0.87	150:1
33	0.93	140:1
35	0.99	130:1
38	1.08	120:1
41	1.16	110:1
45	1.28	100:1