

PRESOAKS & DETERGENTS (HIGH pH)

B a

Product Code:

30010095
30010172
30010171
30010144

Product Application:

Presoak, Tire Cleaner, Wheel Cleaner

Description:

High active foaming alkaline presoak. Contains additional solvents for difficult cleaning situations. Recommended for use in soft water.

Dilution Recommendations:

	<u>Standard</u>	<u>2x</u>	<u>3x</u>
Presoak	60-120:1	120-240:1	180-360:1
Tire and Wheel Cleaner	10-30:1	20-40:1	30-60:1

STANDARD PRODUCT

- Step 1:** Fill graduated cylinder to 5 ml. Mark with solution.
- Step 2:** Add 4 drops Indicator P. Solutions will turn pink.
- Step 3:** Add Titrate #1 drop wise. Invert tube to mix after each drop.
- Step 4:** Continue adding drops until solution turns colorless

Dilution Range: 250:1 - 8:1
Indicator: P
Titrate #: 1

# Drops	OZ. Per Gal.	Ratio:
2	0.52	250:1
3	0.79	163:1
4	1.05	121:1
5	1.32	97:1
6	1.59	80:1
7	1.86	69:1
8	2.12	60:1
9	2.39	54:1
10	2.66	48:1
11	2.92	44:1
12	3.19	40:1
13	3.46	37:1
14	3.72	34:1
15	3.99	32:1
16	4.26	30:1
19	5.06	25:1
24	6.39	20:1
32	8.53	15:1
47	12.54	10:1
60	16.00	8:1

2 P O

- t 1: Fill graduated cylinder to 5 ml. Mark with solution.
- t 2: Add 4 drops Indicator P. Solutions will turn pink.
- t 3: Add Titrate 1 drop wise. Invert tube to mix after each drop.
- t 4: Continue adding drops until solution turns colorless

Dilution Range: 500:1 – 16:1
Indicator: P
Titrate #: 1

s	O . P Gal.	at :
2	0.26	500:1
3	0.39	326:1
4	0.53	242:1
5	0.66	194:1
6	0.80	160:1
7	0.93	138:1
8	1.06	120:1
9	1.20	108:1
10	1.33	96:1
11	1.46	88:1
12	1.60	80:1
13	1.73	74:1
14	1.86	68:1
15	2.00	64:1
16	2.13	60:1
19	2.53	50:1
24	3.20	40:1
32	4.27	30:1
47	6.27	20:1
60	8.00	16:1