

PRESOAKS & DETERGENTS (HIGH pH)

HP300

Product Code:
30010146

Description:

Hard water compatible alkaline system cleaner. Formulated with a combination of alkaline cleaners, water conditioning agents and premium surfactants to effectively remove touch road soils in hard water conditions. Hard water stable up to 300:1 at 8 grains hard.

Product Application:
Presoak, Tire Cleaner, Wheel Cleaner

Dilution Recommendations: Standard

Presoak	500-300:1
Tire and Wheel Cleaner	30-60:1

STANDARD PRODUCT

- Step 1:** Fill graduated cylinder to **10ml**. Mark with solution.
- Step 2:** Add **4** drops Indicator **P**. Solutions will turn pink
- Step 3:** Add Titrate #**1** drop wise. Invert tube to mix after each drop.
- Step 4:** Continue adding drops until solution turns colorless.

Dilution Range:	500:1 - 100:1
Indicator:	P
Titrate #:	1

<u># Drops</u>	<u>OZ. Per Gal.</u>	<u>Ratio:</u>
3	0.26	500
4	0.33	388
5	0.41	310
6	0.49	260
7	0.57	225
8	0.65	197
9	0.73	176
10	0.81	159
11	0.88	145
12	0.96	133
13	1.04	123
14	1.12	114
15	1.20	107
16	1.28	100