

PRESOAKS & DETERGENTS (HIGH pH)

Power Wash

Product Code:
40030005

Description:

Powdered foaming alkaline presoak. For use in high pressure and presoak applications as well as a single step tire and wheel cleaner.

Product Application:

High Pressure, Presoak, Tire Cleaner

Dilution Recommendations:

High Pressure
Presoak
Tire Cleaner

Standard

300-400:1
60-120:1
6:1

STANDARD PRODUCT

- Step 1:** Fill graduated cylinder to **5 ml**. Mark with solution.
Step 2: Add **4** drops Indicator **P**. Solutions will turn pink
Step 3: Add Titrate #1 drop wise. Invert tube to mix after each drop.
Step 4: Continue adding drops until solution turns colorless.

Dilution Range: 1000:1 - 50:1
Indicator: P
Titrate #: 1

# Drops	OZ. Per Gal.	Ratio:
2	0.13	1000:1
3	0.20	635:1
4	0.27	469:1
5	0.34	372:1
6	0.42	308:1
7	0.49	263:1
8	0.56	229:1
9	0.63	203:1
10	0.70	182:1
11	0.77	166:1
12	0.85	152:1
13	0.92	140:1
14	0.99	130:1
15	1.06	121:1
16	1.13	113:1
17	1.20	106:1
18	1.27	100:1
20	1.42	90:1
23	1.63	80:1
26	1.85	70:1
30	2.13	60:1
36	2.56	50:1