

Hi pH Detergents

Presoak HWS

Product Code:

30010159
30010158

Description:

Specially formulated hard water stable alkaline presoak. Designed for use in high pressure automatics as part of a single or two step application and as a tunnel presoak. Hard water stable up to 7 grains hardness at 200:1 dilution.

Product Application:

Presoak, Tire & Wheel Cleaner

Dilution Recommendations:

Presoak
Tire & Wheel Cleaner

2x
120-240:1
20-40:1

2x PRODUCT

- Step 1:** Fill graduated cylinder to **5 ml**. Mark with solution.
- Step 2:** Add **4** drops Indicator **P**. Solutions will turn pink
- Step 3:** Add Titrate **#1** drop wise. Invert tube to mix after each drop.
- Step 4:** Continue adding drops until solution turns colorless.

Dilution Range:	500:1 – 16:1
Indicator:	P
Titrate #:	1

# Drops	OZ. Per Gal.	Ratio:
3	0.26	500:1
4	0.40	322:1
5	0.54	239:1
6	0.67	190:1
7	0.81	158:1
8	0.95	135:1
9	1.09	118:1
10	1.23	104:1
11	1.36	94:1
12	1.50	85:1
13	1.64	78:1
14	1.78	72:1
15	1.92	67:1
16	2.05	62:1
20	2.61	50:1
24	3.16	40:1
32	4.26	30:1
47	6.33	20:1
59	8.00	16:1